

Design Tools For Upgrading Underground Infrastructure in a Congested Urban Environment

February 4, 2020





Alison Schreiber, NEORS D
Alan Stadler, Wade Trim
Cathy Findley, Wade Trim
Sam Glovick, Wade Trim




Multiple design tools enhanced the design of underground hydraulic structures for a new relief sewer system in an urban environment

This presentation focuses on Computational Fluid Dynamics (CFD) and enhanced field reconnaissance using a detailed Subsurface Utility Engineering (SUE) program




Agenda

- Project Overview
- Design
 - Diversion Structure R1-D1
 - Hydraulic Analysis & CFD
 - SUE
 - Diversion Structure R6-D1
 - SUE
 - Utility Owner Coordination
- Construction
- Conclusions



Project Context

NEORSRD Sewer District Service Area




Serves:

- 62 municipalities
- >1M residents

Maintains & Operates:

- Interceptor Sewers
- 3 WWTPs



Consent decree

25-yr, \$3.6B program

4B gallons/yr CSO reduction

Tunnels



Plant improvements

Increased system conveyance capacity



Project Overview


- London Road Relief Sewers Project (LNDN)
 - Control CSOs
 - Reduce Surcharging



Existing Conditions



Project Overview




Project Schedule & Current Status

- Design

- Started: December 2016
- Completed: March 2018

- Construction


- Started: July 2018
- Scheduled Completion: July 2020
- \$40M CV



Overall Design Process

- Establish alignment and locate near surface hydraulic structures
 - Hydraulic analysis
 - Anticipated construction methods
 - Geotechnical considerations
 - Existing underground utility impacts
 - Community impacts
- Balance hydraulic performance with construction risk
- Selectively deploy CFD and SUE design enhancement tools
 - When to use?
 - In which order?
 - Why use them at all?

Diversion Structure R1-D1



- Purpose of Structure
- Location Evaluation
- CFD
- SUE


Diversion Structure R1-D1

Structure Purpose:

- Relieve flow from existing interceptor


How achieved:

- Utilize the full conveyance capacity of the existing combined sewer
- Divert excess wet weather flows to relief sewer
- Dissipate energy due to elevation difference



No. 9 Egg shaped sewer (52"W x 66"H)


R1-D1 Location Evaluation



- Hydraulic analysis
- Anticipated construction methods
- Geotechnical conditions
- Existing underground utility impacts
- Community impacts


R1-D1 Site – Location #1 Utilities

- 20" water main
- Electric ductbank
- Telephone ductbank
- Gas lines





LEGEND

█	PROPOSED SEWER
█	SEWER
█	WATER
█	GAS
█	TELEPHONE
█	ELECTRIC



R1-D1 Site – Location #2 Utilities


- 6" water main
- Telephone ductbank
- Gas lines



LEGEND


- PROPOSED SEWER
- SEWER
- WATER
- GAS
- TELEPHONE

R1-D1 Location Evaluation



1

- Optimal hydraulics
- Most utility conflicts



2

- Acceptable hydraulics
- Manageable utility conflicts


3

- Least hydraulic benefit
- Least utility conflicts


Diversion Structure R1-D1

Advance design to 60%, then use additional tools to refine

- CFD modeling
- SUE



R1-D1 ISO



LEGEND

- PROPOSED SEWER
- SEWER
- WATER
- GAS
- TELEPHONE



CFD Modeling Workflow

- Develop 3D model representing structure geometry
 - Autodesk REVIT
- Export 3D model as Stereolithography (STL) file for import into FLOW-3D
- Develop coarse mesh model, define boundary and initial conditions
- Evaluate the sensitivity of the numerical methods
- Refine mesh for additional accuracy and verification of solution convergence

Diversion Structure R1-D1 Refinement Through CFD

Alt 1 - Large chamber with side spill weir (60% design)


- Stagnant area after drop due to momentum over weir
- Large footprint



Diversion Structure R1-D1 Refinement Through CFD

Alt 2 - Decreased chamber length with intermediate step



- High turbulence on step, unsteady flow
- Improved energy dissipation and outlet hydraulics



Diversion Structure R1-D1 Refinement Through CFD

Alt 3 - Decreased chamber length, stepped with dividing walls

- Steady flow through structure
- Improved energy dissipation and outlet hydraulics




SUE Approach

- ASCE Standard 38-02 “Standard Guideline for the Collection and Depiction of Existing Subsurface Utility Data”
- Progression of detail:
 - Level D: records research
 - Level C: above ground survey
 - Level B: utility designation
 - Level A: test hole/pot holing



Diversion Structure R1-D1 SUE


- 5 Level A test holes performed
 - Located top and sides of existing sewers
 - Confirmed underground utility locations
- Coordinated with utility companies



Diversion Structure R1-D1 SUE


Results:

- Unknown gas line was confirmed as abandoned, remove during construction
- Telephone ductbank located, different than record drawings
 - Lowered structure roof
 - Relocated structure riser



R1-D1 Structure Final Configuration

Compact shape
Refined hydraulics
Minimized utility conflicts




LEGEND

	PROPOSED SEWER
	EXISTING SEWER (
	PROPOSED ACCESS OPENING


Diversion Structure R6-D1

Design Refinement

- SUE
- Utility Owner Coordination



Diversion Structure R6-D1



No. 4 egg shaped sewer (39"H x 30"W)


Structure purpose:

- Reduce CSO overflows to Nine Mile Creek


How achieved:

- Divert excess wet weather flows to new relief sewer
- Use conveyance capacity of nearby existing combined system (HHI)

Diversion Structure R6-D1




R6-D1





Diversion Structure R6-D1 SUE

- 12 Level A test holes performed in two rounds
 - Located top and sides of existing sewers
 - Confirmed underground utility locations
- Coordinated with utility companies
 - Electric Company - CEI




Diversion Structure R6-D1 SUE

- Round 1: 7 test holes
 - Horizontal and vertical conflicts with electric ductbanks
- Round 2: 5 test holes
 - Reduced vertical conflict




Diversion Structure R6-D1 Electric Utility Coordination


- 12 Duct system
 - Can be relocated horizontally
- 9 duct system
 - Top 3 ducts are vacant, can relocate vertically




R6-D1 Plan



R6-D1 Electric Ductbank Locations



R6-D1 Plan



R6-D1 Results of SUE and Utility Coordination


SUE

- Confirmed horizontal and vertical locations of utilities
 - 1st round – revise layout
 - 2nd round – viable

Utility coordination

- Corroborated SUE information
(from MH inspections & records)
- Confirmed vacant ducts
- Allowed R6-D1 Structure to be cast against existing Electric Vault
- Estimated relocation costs


R6-D1 Final Configuration




R6-D1 Plan



Construction?




Pipe Installation & Duct Bank Relocation





Conclusions

- Designs can be enhanced by selectively using targeted tools
- Use tools at appropriate times
 - Collection system modeling
 - CFD modeling
 - SUE
 - Coordination with utility owner(s)
- Additional cost during design yields reduced risk and cost during construction



Thank you!

Questions?



Alan Stadler, PhD, PE, Conveyance Practice Lead
1100 Superior Avenue East, Suite 1710, Cleveland, OH 44114
216.363.0300 office
216.317.6662 cell



Additional reference slides not presented follow this one.

FLOW  **Science**[®]
FLOW-3D[®]


 **Cardno**


TRIAD
Cleveland, OH Charleston, SC

 **C&M McNALLY**
TUNNEL CONSTRUCTORS

Fabrizi

NORTHSTAR
BUILDING EXCELLENCE STARTS WITH INTEGRITY



Reach	Excavated Diameter	Finished ID
1	112"	72" / Roseland / 66" RCP
2	83"	42" HOBAS
3	83"	48" RCP


R1-D1 Site – Location #3 Utilities

- 6" water main
- Telephone ductbank
- Gas lines




LEGEND


- PROPOSED SEWER
- SEWER
- WATER
- GAS
- TELEPHONE




Diversion Structure R6-D1

- Purpose of Structure
- Sewer Alignment/Connectivity
- SUE
- Utility Owner Coordination





Diversion Structure R6-D1



Exiting R6-D1 and conveying WWF down Hillsboro

Hobas (R6-D1 to R6-M1)



RCP (downstream of R6-M1)

